



FEDERATION  
INTERNATIONALE  
DE L'AUTOMOBILE  
WWW.FIA.COM

2024

# SFI - Specifications for FIA Drag Racing

The following list shows all SFI Specifications used in FIA Drag Racing with their respective recertification periods.

An item with a recertification period must be sent back to the original manufacturer or his agent at the end of this time frame for inspection before it can be permitted for further use at an FIA/ASN sanctioned Event.

Spec.	Product Description	Recertification Period
1.1	Single Disc Clutch & Flywheel Assembly	4 years
1.2	Multiple Disc Clutch Assemblies for Vehicles with Naturally Aspirated Engines	4 years
1.3	Nitro-Methane Drag Race Multiple Disc Clutch Assemblies	2 years
1.4	Methanol Drag Race Multiple Disc Clutch Assemblies	2 years
1.5	Multiple Disc Clutch Assemblies for Supercharged, Nitrous Oxide-injected, and Turbocharged Vehicles	2 years
2.1	Rear Engine Dragster Roll Cage – 5.99 Seconds & Quicker, TM/D (Includes Wing and Rear-End Mounting)	N/A
2.2	Front Engine Dragster Roll Cage - 5.99 Seconds & Quicker, TM/D	N/A
2.3	Rear-Engine Dragster Chassis Spec, TF (include Wing and Rear-End Mounting)	N/A
2.4	Front Engine Dragster Roll Cage – 6.00 to 7.49 Seconds	N/A
2.5	Rear Engine Dragster Roll Cage – 6.00 to 7.49 Seconds	N/A
2.6	Front Engine Dragster Roll Cage – 7.50 Seconds & Slower	N/A
2.7	ET Rear Engine Dragster Roll Cage – 7.50 Seconds & Slower	N/A
3.2A/1	Drivers Suits	N/A
3.2A/5	Drivers Suits	N/A
3.2A/15	Drivers Suits	N/A
3.2A/20	Drivers Suits	N/A
3.3	Arm Restraints, Hoods/Balaclavas, Socks, Underclothing, Sports Bras, Harness Pads, Helmet Supports	N/A
3.3/1	Gloves, shoes	N/A
3.3/10	Helmet skirt, Gloves	N/A
3.3/5	Helmet skirt, Gloves, Shoes, Boots	N/A
3.3/15	Gloves, Boots	N/A
3.3/20	Gloves, Boots	N/A
4.1	Automatic Transmission Shield; Rigid	5 years
4.1	Automatic Transmission Shield; Flexible	5 years
6.1	Containment Bellhousing for SFI 1.1 & 1.2 Clutch Assemblies for limited normally aspirated applications, and forced induction applications with torque converters	Bellhousing must be recertified according to the manufacturer Sticker on the Bellhousing
6.1W	Passenger Car Replacement Containment Bellhousing with Adjustable Clutch Window for SFI 1.1 & 1.2 Clutch Assemblies for limited normally aspirated applications, and forced induction applications with torque converters	Bellhousing must be recertified according to the manufacturer Sticker on the Bellhousing
6.2	Containment Bellhousing for SFI 1.3 & 1.4 Clutch Assemblies for Nitro-methane, Top Methanol	Bellhousing must be recertified according to the manufacturer Sticker on the Bellhousing
6.3	Containment Bellhousing for SFI Clutch Assemblies for supercharged and nitrous-oxide applications	Bellhousing must be recertified according to the manufacturer Sticker on the Bellhousing
7.1	Lower Engine Containment Device	N/A
7.2	Sportsman Lower Engine Containment Device	N/A
9.1	Sport Compact Bellhousing Blanket	5 years
10.1	Funny Car Roll Cage (TM/FC, Advanced ET, etc.)	N/A
10.2	Altered Car Roll Cage, 6.00 to 7.49 Second E.T.	N/A
10.3	Altered Car Roll Cage, 7.50 Seconds and Slower E.T.	N/A
10.4	Side Steer Roadster Roll Cage - 7,50 & Slower	N/A
10.5	Fuel Funny Car Roll Cage Chassis – 4.99 Seconds and quicker	N/A

Spec.	Product Description	Recertification Period
14.1	Supercharger Restraint (Roots); ET, Adv. ET	4 years
14.2	Supercharger Restraint (Roots); P/M, TM/D, TM/FC, FC	4 years
14.21	Supercharger Restraint (Screw type); Adv. ET, TM/D, TM/FC	4 years
14.3	Supercharger Restraint (Roots); TF	4 years
14.4	Valve Cover Restraint	4 years
14.5	Manifold Blankets	4 years
15.1	Drive Wheels	N/A
15.2	Front wheels; FC, TF	N/A
15.3	High Horsepower Rear-drive wheels	4 years
15.4	Rear-Drive Bead lock Wheels - FC, TF	2 years
16.1	Driver Restraint System	2 years
16.2	Restraint Assemblies for youth Drivers	2 years
16.5	Driver Restraint System	2 years
16.6	Advanced Motorsport Restraint Assemblies	2 years
17.1	Onboard Fire Suppression Systems	2 years
18.1	Harmonic Balancer	N/A
23.1	Manifold Burst Panel	N/A
25.1	Full Body Chassis; Adv. E.T, P/M, PS – 7.49 Seconds and quicker, 2,800 lbs Max.	N/A
25.2	Full-Bodied Car Tube Chassis Roll Cage – 6.00 to 7.49 Seconds; 3,200 lbs. Max.	N/A
25.3	Full Bodied Car with Aftermarket Body Shell and Tube Frame, OEM Body Shell and OEM Frame with OEM or Modified Floor pan and Firewall, or Uni-Body with OEM or Modified Floor pan and Firewall Roll Cage - 6.50 to 7.49 Seconds ET; 3,600 Lbs. Max.	N/A
25.4	Full Bodied Car Tube Chassis Roll Cage - 7.50 to 8.49 Seconds ET; 3,600 lbs. Maximum	N/A
25.5	Full Bodied Car Stock or Modified/OEM Floor pan and Firewall with OEM Frame or Uni-Body Construction - 7.50 to 8.49 Seconds ET; 3,600 lbs. Max.	N/A
25.6	Full Bodied Car Stock / Truck or Modified/OEM Floor pan and Firewall with OEM Frame or Uni-Body Construction – 7.99 to 8.49 Seconds E.T.; 5,000 lbs. Maximum	N/A
27.1	Window Net (Mesh or Ribbon)	N/A
28.1	Fuel Cell	N/A
28.2	Crash Resistant Fuel Cell	N/A
28.3	Competition Fuel Cell Bladder	5 years
29.1	Automatic Transmission Flex plate	3 years
29.2	High Horsepower Automatic Transmission Flex plate	3 years
29.3	Automatic Transmission Flex plate for Diesel Applications	3 years
30.1	Automatic Transmission Flex plate Shield	5 years
34.1	Supercharger, Screw Type	3 years
38.1	Head and Neck Restraint Systems	5 years
42.1	Steering Wheel - Quick Disconnect / Release	N/A
43.1	Driveshaft	N/A
45.1	Roll Bar / Cage Padding	N/A
45.2	Impact Padding/Head Surround	N/A
49.1	Top Fuel Rear Wing Assembly	5 years
49.2	Top Fuel Front Wing Assembly	5 years
54.1	Coatings	N/A
61.1	Turbochargers – P/M	5 years